
FN990A40/A28

5G/LTE



Product Description

The Telit FN990A40 and FN990A28 data cards enable a new generation of 5G state-of-the-art data cards featuring sub-6 only technology with LTE, WCDMA and GNSS support. These data cards lay the foundation for businesses worldwide to future-proof IoT, enterprise applications and video while leveraging all 5G's and Gigabit LTE's benefits immediately.
The industrial-grade M.2 form factor is suitable for many high-performance and bandwidth-intensive enterprise and industrial applications. Use cases include fixed wireless access, enterprise routers and gateways, indoor and outdoor CPE, professional broadcasting and surveillance.

Designed for global usage, the FN990A40 and FN990A28 incorporate support for all scenarios prescribed by the 3GPP Rel.16 deployments of 5G, including non-standalone (NSA) LTE-5G NR dual connectivity (EN-DC), dynamic spectrum sharing between LTE and 5G and full 5G NR standalone (SA) mode.

Leveraging the full feature set of the groundbreaking fourth-generation Qualcomm® Snapdragon™ X65 and Snapdragon™ X62 5G Modem-RF System, the Telit data cards support the latest 5G deployments.

The FN990A40 and FN990A28 supports all major sub-6 GHz frequency bands, giving users maximum deployment flexibility.
The FN990A40 data card is based on Qualcomm® Snapdragon™ X65 targeting high-tier market needs. The FN990A28 data card is based on Qualcomm® Snapdragon™ X62 targeting mid-tier market needs.

Key Benefits

- Support of 5G sub-6 FDD and TDD for global deployment
- Support of SA and NSA operations, 5G core network Opt. 3a/3x and Opt. 2 for full network compatibility
- Latest generation 4G/5G Rel.16
- 4G Cat 20 up to 7 CA for FN990A40
  4G Cat 19 up to 5 CA for FN990A28
- Intraband and interband UL CA supported on 4G networks for better throughput performance for uplink-centric applications, like surveillance cameras and 4K/8K video streaming
- 3G HSPA+ Rel. 8 for fallback to legacy networks
- Standard M.2 (NGFF) data card form factor
- Support for both PCIe Gen 3 and USB 3.1 Gen 2 for maximum application design flexibility
- Dedicated/shared (switchable) RF path/connector for GNSS L1 to allow total flexibility in the design phase and low losses whenever high sensitivity is required
- Internal GNSS L1 LNA allowing the use of less expensive passive antennas, lowering the total cost of ownership

AVAILABLE FOR

NA
EMEA
APAC

FN990A40/A28

Variants

	FN990A40/A28
Market	North America, EMEA, APAC
5G FR1 bands	n1, n2, n3, n5, n7, n8, n20, n25, n28, n30, n38, n40, n41, n48, n66, n71, n75, n77, n78, n79 NSA default off - n12, n13, n14, n18, n26, n29, n76 SA default off - n12, n13, n14, n18, n26, n29, n76
5G FR1 bandwidth	200 MHz, 3CC CA DL
5G FR2	N/A
LTE	B1, B2(B25), B3, B4(B66), B26(B5, B18, B19), B7, B8, B12(B17), B13, B14, B20, B28, B29(DL), B30, B32(DL), B34, B38, B39, B40, B41, B42, B43, B46(LAA), B48(CBRS), B66, B71
WCDMA	B1, B2, B4, B5(B6, B19), B8 (for EU and APAC regions only)
Approvals	FCC, IC, RED, NCC, JATE/TELEC, KC, RCM, PTCRB, GCF, Various MNOs

Product Features

- 5G sub-6 FDD and TDD, SA and NSA operations
- 5G core network Opt. 3a/3x and Opt. 2
- 4G: 7 CA up to 20 layers DL/2 CA UL, 256-QAM DL/UL for FN990A40
  4G: 5 CA up to 19 layers DL/2 CA UL, 256-QAM DL/UL for FN990A28
- 3G: HSPA+ Rel. 8 (DL/UL 42/11 Mbps)
- GNSS: gpsOne Gen 9 Band L1 on dedicated RF connector
- 4x4 MIMO DL support on bands:
  5G FR1: n1/n2/n3/n7/n25/n30/n38/n40/n41/n48/n66/n75/n77/n78/n79
  4G: B1/B2/B3/B4/B7/B25/B30/B38/B39/B40/B41/B42/B43/B48/B66
- 2x2 MIMO UL support on bands: 5G FR1:n38,n41, n48, n77, n78, n79
- Antenna types: four LTE/sub-6 + one GNSS
- FOTA support
- Support of SIB9-based network time communication

Hardware and Electrical Specifications

- Dimensions: 30 × 52 × 2.25 mm
- 1.8/3 V SIM Interface
- USB 3.1 Gen 2
- PCIe Gen3 - one lane
- Drivers support: Windows 10, Linux
- Operating temperature range: -40 °C to +85 °C
- LTE/5G sub-6 output power
  - 23 dBm (Power Class 3)
  - 26 dBm (Power Class 2 in B41/n41)
- Supply voltage
  - Nominal: 3.3 V dc

Data Throughput

- 5G NSA up to:
  4.9 Gbps DL / 0.55 Gbps UL for FN990A40
  3.4 Gbps DL / 0.46 Gbps UL for FN990A28

  5G SA up to:
  4.1 Gbps DL / 0.90 Gbps UL for FN990A40
  2.5 Gbps DL / 0.90 Gbps UL for FN990A28
- 4G up to:
  2.0 Gbps DL / 211 Mbps UL for FN990A40
  1.6 Gbps DL / 211 Mbps UL for FN990A28
- 3G up to 42 DL/11 UL Mbps

QUESTIONS? VISIT WWW.TELIT.COM/CONTACT-US

Like Us on Facebook | Follow Us on LinkedIn | Follow Us on Twitter | Subscribe to Our Channel

[08.2023]

Telit Cinterion reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. The information contained herein is provided "as is." No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by Telit Cinterion at any time. For most recent documents, please visit www.telit.com.

Copyright © 2023, Telit Cinterion